



BOSCH

PROFESSIONAL BLUE POWER TOOLS FOR TRADE AND INDUSTRY 2022



Edition: March 2022




BeConnected is a simple way for users to stay connected through product registration


Avail the best-in-class Bosch products with all the exciting benefits such as Paperless Warranty, Warranty Extension, Reward Points*, Cash Back*, Product Information and Seamless After Sales Service




Scan the QR code on the label of your power tool




Register on BeConnected and get benefited



Receive E-warranty instantly



Get product information, tutorial videos, customer reviews and more



You can even get discount coupons!



Simply scan and enjoy a world of benefits

BENEFITS

Anti-Counterfeit

Certified Bosch-made products only

Product Info (Video)

Valuable demos and tutorials on the product

Warranty Certificate

Quality products with certified assurances

Where to Buy / Service

Locate the nearest Bosch dealer to you

Promotions / Coupons

Win exciting rewards and prizes

Fleet Management

Manage your entire portfolio of products

Communication / Bosch Power Tools

Stay up to date with the latest from Bosch Power Tools

Ratings & Reviews

Share your valuable experience with us and your peers

* T&C Apply, Periodic promotions

CORDLESS



SCREWDRIVER

Bosch GO 2.0 Professional




Technical Specifications

HSN code	84672100
Part no.	0 601 9H2 1L1
Battery voltage	3.6 V
Torque, max. (hard/soft)	5 / 2.5 Nm
No-load speed	360 rpm
Electronic brake	Yes
Smart stop	Yes
Tool holder	¼" Inter HEX

Scope of supply:
1 USB cable;
PH1 & PH2 screw bit

MRP: ₹ 4,900



SCREWDRIVER

Bosch GO 2.0 Kit Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9H2 181
Battery voltage	3.6 V
Torque, max. (hard/soft)	5 / 2.5 Nm
No-load speed	360 rpm
Electronic brake	Yes
Smart stop	Yes
Tool holder	¼" Inter HEX
Weight excl. battery	0.31 kg

Scope of supply:
Carrying case; Micro USB cable;
33-piece screwdriver bit set

MRP: ₹ 5,300



DRILL DRIVER

GSR 120-Li (Single Battery) Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9G8 0F1
Battery voltage	12 V
No-load speed	0-400 / 0-1,500 rpm
Torque, max. (hard/soft)	30 / 14 Nm
Max. screw diameter	7 mm
Chuck size	10 mm
Drilling in wood/metal	20 / 10 mm
Weight incl. battery	0.97 kg

Scope of supply:
1 x 12V 2 Ah Li-ion battery;
1 Charger

MRP: ₹ 6,800



DRILL DRIVER

GSR 120 Li Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9G8 0F0
Battery voltage	12 V
No-load speed (1st/2nd)	0 - 400 / 0 - 1,500 rpm
Torque (hard/soft)	30 / 14 Nm
Max. screw diameter	7 mm
Max. drilling (wood/steel)	20 / 10 mm
Chuck size	10 mm

Scope of supply:
2 x 12V 2 Ah Li-ion batteries,
1 Charger, Carry case,
Accessory set, 6 Metal drill bit,
4 Wood drill bit, 10 Screw driver
bit and 1 Screw driver bit holder

MRP: ₹ 10,900



DRILL DRIVER

GSR 12V-30 (Solo) Professional

1

CORDLESS



Technical Specifications

HSN code	84672100
Part no.	0 601 9G9 082
Battery voltage	12 V
No-load speed	0-420 / 0-1,600 rpm
Torque, max. (hard/soft)	30 / 18 Nm
Max. screw diameter	8 mm
Max. drilling (wood/steel)	20 / 10 mm

Scope of supply:
Carrying case;
*Battery and charger not included

MRP: ₹ 9,500



DRILL DRIVER

GSR 12V-35 HX (Solo) Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9J9 180
Battery voltage	12 V
No-load speed (1st/2nd)	0 - 460 / 0 - 1,750 rpm
Torque (soft/hard)	20/35/- Nm
Max. screw diameter	8 mm
Max. drilling (wood/steel)	32 / 10 mm
Chuck capacity, min./max.	0.8 / 10 mm
Weight excl. battery	0.57 kg

Scope of supply:
Carrying case;
*Battery and charger not included

MRP: ₹ 10,800



DRILL DRIVER

GSR 12V-15 FC Professional



*Product available till stocks last



Technical Specifications

HSN code	84672100
Part no.	0 601 9F6 0F0
Battery voltage	12 V
No-load speed (1st/2nd)	0 - 400 / 0 - 1,300 rpm
Torque (hard/soft)	30 / 15 Nm
Max. screw diameter	7 mm
Max. drilling (wood/steel)	19 / 10 mm
Chuck size	10 mm

Scope of supply:
Drill chuck adapter GFA 12-B;
Off-set angle adapter GFA 12-E;
Angle adapter GFA 12-W;
Hex adapter; 1 Charger;
2x2 Ah Li-ion batteries; Carry case

MRP: ₹ 24,500



DRILL DRIVER

GSR 180-Li Professional



*Product available till stocks last



Technical Specifications

HSN code	84672100
Part no.	0 601 9F8 1F0
Battery voltage	18 V
No-load speed (1st/2nd)	0 - 450 / 0 - 1,700 rpm
Torque (hard/soft)	54 / 21 Nm
Max. screw diameter	10 mm
Max. drilling (wood/steel)	35 / 10 mm
Chuck size	13 mm

Scope of supply:
2 x 2 Ah Li-ion batteries;
1 Charger; Carry case

MRP: ₹ 16,900



DRILL DRIVER

New! GSR 185-Li Professional



Technical Specifications

HSN code	84672100
Battery voltage	18 V
Head length	162 mm
No-load speed	0-500 / 1,900 rpm
Max. torque (hard / soft)	50 / 21 Nm
Max. screw diameter	10 mm
Max. drilling (wood/metal)	35 / 10 mm
Weight (w/2.0Ah)	1.3 kg

Scope of supply:
2 x 2 Ah Li-ion batteries;
1 Charger; Carry case



DRILL DRIVERS

GSR 18V-50 (Solo) Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9H5 082
Battery Voltage	18 V
No-load speed (1 st gear / 2 nd gear)	0 - 460 / 0 - 1,800 rpm
Torque (soft/hard/max.)	28/50/50 Nm
Max. screw diameter	10 mm
Max. drilling (alum/wood/steel)	13 / 35 / 13 mm
Weight excl. battery	1 kg

Scope of supply:
Cardboard box;
*Battery and charger
not included

MRP: ₹ 12,950



DRILL DRIVER

GSR 18V-50 Kit Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9H5 0F0
Battery voltage	18 V
No-load speed	0 - 460 / 0 - 1,800 rpm
Torque, max. (hard/soft)	50 / 28 Nm
Max. drilling (wood/steel)	35 / 13 mm
Max. screw diameter	10 mm

Scope of supply:
Carry case; 1 Charger;
2 x 2.0 Ah Li-ion batteries

MRP: ₹ 24,480



IMPACT DRILL DRIVERS

GSB 120-Li Kit Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9G8 1F2
Battery voltage	12 V
No-load speed (1 st /2 nd)	0 - 400 / 0 - 1,500 rpm
Torque (hard/soft)	30 / 14 Nm
Impact rate	0 - 18750 bpm
Max. drilling (wood/steel/masonry)	20 / 10 / 8 mm
Weight with battery	1.1 kg

Scope of supply:
Carry case; 1 Charger;
2 x 2 Ah Li-ion batteries;
Accessory set: 4 Wood drill bits;
4 Metal drill bits; 4 Masonry drill
bits; 10 Screw driver bits;
1 Screw bit holder

MRP: ₹ 11,856





BITURBO
BRUSHLESS

IMPACT DRILL DRIVERS

GSB 180-Li Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9F8 3F0
Battery voltage	18 V
No-load speed (1 st /2 nd)	0 - 450 / 0 - 1,700 rpm
Torque (hard/soft)	54 / 21 Nm
Max. screw diameter	10 mm
Max. drilling (wood/steel/masonry)	35 / 10 / 8 mm
Chuck size	13 mm

Scope of supply:
2 x 2 Ah Li-ion batteries;
1 Charger; Carry case

MRP: ₹ 17,800



DRILL DRIVER

New! GSB 18V-150 C (Solo) Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9J5 1L0
Battery voltage	18 V
Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1 st / 2 nd gear)	0 - 550 / 0 - 2,200 rpm
Max. impact rate	30,000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Weight excl. battery	2.2 kg

Scope of supply:
*Battery and charger
not included

MRP: ₹ 27,000



IMPACT WRENCH

GDR 120-Li Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9F0 0F0
Battery voltage	12 V
No-load speed (1 st /2 nd)	0 - 1,300 / 0 - 2,600 rpm
Torque (hard)	100 Nm
Max. screw diameter	8 mm
Rated impact rate	0 - 1,900 / 0 - 3,200 bpm
Bit holder	1/4" hexagon socket

Scope of supply:
2 x 2.0 Ah Li-ion batteries,
1 Charger, 1 Carry case

MRP: ₹ 15,000



IMPACT WRENCH

GDR 12 V-EC Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9E0 0F6
Battery voltage	12 V
No-load speed	2,600 rpm
Torque (hard)	110 Nm
Max. screw diameter	M 4 - M 12
Rated impact rate	0 - 3,100 bpm
Bit holder	1/4" internal hexagon

Scope of supply:
Carry case; 2 x 2 Ah Li-ion
batteries; 1 Charger

MRP: ₹ 24,800



IMPACT WRENCH

New! GDR 180-Li Professional

1



Technical Specifications

HSN code	84672100
Part no.	0 601 9G5 1F0
Battery voltage	18 V
No-load speed	0 - 2,800 rpm
Impact rate	0 - 3,600 bpm
Max. torque	160 Nm
Tool holder	1/4" Hex Uni
Screw diameter	M 6 – M 14
Weight excl. battery	1.1 kg

Scope of supply:
2 x 2.0 Ah Li-ion batteries;
1 Charger

MRP: ₹ 26,400



CORDLESS

IMPACT WRENCH

GDX 18V-200 C Professional




Technical Specifications

HSN code	84672100
Part no.	0 601 9G4 2F0
Battery voltage	18 V
Torque max.	200 Nm
No-load speed	0 - 3,400 rpm
Rated impact rate	0 - 4,000 bpm
Bit holder	1/4" internal hexagon and 1/2" external square
Weight excl. battery	1.1 kg

Scope of supply:
Carry case; 1 Charger;
2 x 4.0 Ah Li-ion batteries

MRP: ₹ 35,650



IMPACT WRENCH

GDS 18V-200 Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9J2 3F0
Battery voltage	18 V
Square drive	1/2 inch
No-load speed	0 - 3,400 rpm
Impact rate	0 - 4,200 bpm
Max. torque	200 Nm
Screw diameter	M 6 – M 16
Weight excl. battery	1.1 kg

Scope of supply:
2 x 4.0 Ah Li-ion batteries;
1 Charger

MRP: ₹ 31,000



IMPACT WRENCH

GDS 250-Li Professional




Technical Specifications

HSN code	84672100
Part no.	0 601 9G6 1F0
Battery voltage	18 V
Max. torque	250 Nm
No-load speed	0 - 2,400 rpm
Impact rate	0 - 3,300 bpm
Tool holder	1/2" Square
Screw size	M10 ~ M18
Weight excl. battery	1.2 kg

Scope of supply:
2 x 4.0 Ah Li-ion batteries;
1 Charger

MRP: ₹ 31,200



IMPACT WRENCH

GDS 18V-400 Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 9K0 0F0
Battery voltage	18 V
Max. declared torque	400 Nm
Square drive	1/2 inch
No-load speed	0 - 2,500 rpm
Impact rate	0 - 3,700 bpm
Head length	172 mm
Weight (w/o battery)	1.25 kg
Weight (w GBA 18V 5.0Ah)	1.85 kg

Scope of supply:
Carry case; 1 Charger;
2 x 5.0 Ah Li-ion batteries

MRP: ₹ 42,750



IMPACT WRENCH

GDS 18V-1050 H Professional



BITURBO
BRUSHLESS



Technical Specifications

HSN code	84672900
Part no.	0 601 9J8 5F0
Battery voltage	18 V
Max. tightening torque	1,050 Nm
Max. breakaway torque	1,700 Nm
Square drive	3/4 inch
No-load speed	0-800/1,200/1,750 rpm
Impact rate	0-1,600/2,400/2,600 bpm
Torque	0.350 / 750 / 1050
Bolt diameter	M10 - M24
Weight (w/o battery)	2.9 kg

Scope of supply:
1 Charger;
2 x 5.0 Ah Li-ion batteries;
L-BOXX 136

MRP: ₹ 57,700



ROTARY HAMMER 1-2 KG

GBH 180-Li (Brushless) Professional



Technical Specifications

HSN code	84672900
Part no.	0 611 911 1F0
Battery voltage	18 V
Impact force	2.0 J
Drilling capacity	20 mm
No-load speed	0 - 1,800 rpm
Impact rate	0 - 4,550 bpm
Brushless motor	Yes
LED light	Yes
Max. drilling diameter in wood:	30 mm
Max. drilling in metal:	13 mm
Weight (bare tool)	2.4 kg

Scope of supply:
1 Charger;
2 x 4 Ah Li-ion batteries

MRP: ₹ 38,100



ROTARY HAMMER 4 KG

GBH 18V-34 (Solo) Professional



BITURBO
BRUSHLESS



Technical Specifications

HSN code	84672900
Part no.	0 611 914 082
Battery voltage	18 V
Max. impact energy	5.8 J
Rated speed	0 - 500 rpm
Impact rate at rated speed	0 - 2,900 bpm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	40 mm
Max drilling diameter in concrete	34 mm
Weight excluding battery	4.9 kg

Scope of supply:
*Battery & charger not included MRP: ₹ 72,850



SMALL ANGLE GRINDER

GWS 18V-10 (100 mm) KIT Professional

1

CORDLESS



Technical Specifications

HSN code	84672900
Part no.	0 601 9J4 0F0
Battery voltage	18 V
Grinding spindle thread	M 10
No-load speed	9,000 rpm
Weight w/o battery	2.0 kg

Scope of supply:
2 x 5.0 Ah Li-ion Batteries;
1 Charger; Handle; Keyless protection guard; Clamping unit

MRP: ₹ 41,200



SMALL ANGLE GRINDER

GWS 180-Li Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 9H9 0F0
Battery voltage	18 V
No-load speed (1 st /2 nd)	11,000 rpm
Spindle size	M10
Disc diameter	100 mm
Grip size front / back	185 / 156
Weight w/o battery	1.4 kg
Weight w/ 4.0 battery	2.0 kg

Scope of supply:
Standard auxiliary handle; Keyless Protection guard;
Clamping nut; Back flange; Tom hole spanner;
2 x 4.0 Ah Li-ion Batteries;
GAL 18V-40 charger x 1

MRP: ₹ 34,100



SMALL ANGLE GRINDER

GWS 180-Li (Solo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 9H9 0K0
Battery voltage	18 V
No-load speed (1 st /2 nd)	11,000 rpm
Spindle size	M10
Disc diameter	100 mm
Grip size front / back	185 / 156
Weight w/o battery	1.4 kg
Weight w/ 4.0 battery	2.0 kg

Scope of supply:
*Battery and charger not included

MRP: ₹ 14,450



SMALL ANGLE GRINDER

GWS 18V-10 (125 mm) (Solo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 9J4 002
Battery voltage	18 V
No-load speed	9,000 rpm
Grinding/cutting disc, diameter	125 mm
Grinding spindle thread	M14
Weight excluding battery	2.1 kg

Scope of supply:
Cardboard box;
*Battery and charger not included

MRP: ₹ 18,850



Improved pruning efficiency, with the pull of a trigger!



Sharp and durable blades which always cut cleanly



Easy and safe to use with double safety switch



4500 cuts from just 1 hour of fast charging



Portable and lightweight for continuous use



BLOWER

GBL 18V-120 (Solo) Professional

1



Technical Specifications

HSN code	84672900
Part no.	0 601 9F5 1L0
Battery voltage	18 V
Max. air speed	75 m/s
Max. airflow	120 m³/h
No-load speed	17,000 rpm
Weight excluding battery	1.1 kg

Scope of supply:
4 x Accessories (Nozzle, Extension tube, Deep hole nozzle, Dust collection tube)
*Battery and charger not included

MRP: ₹ 8,550



CORDLESS

CUTTING

New! Pro Pruner Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 9K1 0F1
Rated voltage	12 V
Battery capacity*	3 Ah
Max. cutting diameter	25 mm
No. of cuts per charge**	4500
Weight with 12V/2.0Ah battery	1 kg
Weight w./o battery	0.8 kg

Scope of supply:
1 x 12V 2 Ah Li-ion battery;
1 Charger

MRP: ₹ 20,720



CIRCULAR SAWS

GKS 18V-57 (Solo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 6A2 2L0
Battery voltage	18 V
No-load speed	3,400 rpm
Saw blade diameter	165 mm
Saw blade bore diameter	20 mm
Max. cutting capacity in wood (90°)	57 mm
Max. cutting capacity in wood (45°)	39 mm

Scope of supply:
1 x circular saw blade;
Optiline wood;
*Battery charger not included

MRP: ₹ 21,200



ALL PURPOSE / RECIPSAW

GSA 18V-Li Compact (Solo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 6A5 080
Battery voltage	18 V
Cutting depth in wood	200 mm
Stroke lengths	21 mm
Cutting depth in metal profiles and metal pipes	100 mm
Stroke rate (1st gear / 2nd gear)	0 - 3,050 spm

Scope of supply:
*Battery and charger not included
Cardboard box; Inlay for L-BOXX 136;
1 x reciprocating saw blade S 922 AF,
1 x reciprocating saw blade S 922 EF,
1 x reciprocating saw blade S 922 HF

MRP: ₹ 24,600



ALL PURPOSE / RECIPSAW

GSA 18V-32 (Solo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 6A8 108
Cutting depth in wood	230 mm
Stroke lengths	32 mm
Cutting depth in metal profiles and metal pipes	175 mm
Stroke rate (1st gear / 2nd gear)	0 - 2,500 spm
Weight excl. battery	3.5 kg

Scope of supply:

*Battery and charger not included

Cardboard box;

1 x reciprocating saw blade

S 1110 VF

MRP: ₹ 56,650



BATTERY / CHARGERS

CHARGERS/
BATTERIES



BATTERY

GBA 12V 2.0 Ah Professional



Technical Specifications

HSN code	85076000
Part no.	1 600 A00 F6X
Battery voltage	12 V
Battery capacity	2 Ah
Weight	175 g

Suitable for

- 10.8 V
- 12.0 V

Bosch cordless tools range
(Tubular battery version)

MRP: ₹ 3,400

BATTERY

GBA 18V 2.0 Ah Professional



Technical Specifications

HSN code	85076000
Part no.	1 600 A00 1CG
Battery voltage	18 V
Battery capacity	2 Ah
Weight	300 g

Suitable for

- All 18 V

Bosch cordless tools range

MRP: ₹ 5,500

BATTERY

GBA 18V 4.0 Ah Professional



Technical Specifications

HSN code	85076000
Part no.	1 600 A00 163
Battery voltage	18 V
Battery capacity	4 Ah
Weight	600 g

Suitable for

- All 18 V

Bosch cordless tools range

MRP: ₹ 8,300

BATTERY

New! ProCORE 18V 4.0 Ah Professional



Technical Specifications

HSN code	85076000
Part no.	1600A0193L
Battery voltage	18 V
Battery capacity	4 Ah
Weight	515 g

Suitable for

- All 18 V

Bosch cordless tools range

MRP: ₹ 10500

BATTERY

New! ProCORE 18V 8.0 Ah Professional



Technical Specifications

HSN code	85076000
Part no.	1600A0193N
Battery voltage	18 V
Battery capacity	8 Ah
Weight	955 g

Suitable for

- All 18 V

Bosch cordless tools range

MRP: ₹ 19500

CHARGER

GAL 12V-40 Professional



Technical Specifications

HSN code	85044030
Part no.	1 600 A02 2V0
Charge current	4 A
Charging time min.	24 min
Input voltage	230 V
Model	Li-Ion quick charger
Weight, approx.	0.4 kg

MRP: ₹ 3,100

Suitable for charging of

- 10.8 V
- 12.0 V

Bosch tubular batteries

CHARGER

GAL 18V-40 Professional



Technical Specifications

HSN code	85044030
Part no.	1 600 A02 2V1
Battery charging voltage	14.4 – 18 V
Charge current	4 A
Charging time min.	36 min
Model	Li-Ion quick charger
Weight, approx.	550 g

MRP: ₹ 4,000

Suitable for charging of

- 14.4 V
- 18.0 V

STARTER KITS

GAL 12V-40 + 2x GBA 12V 2.0Ah Professional



Technical Specifications

HSN code	85044030
Part no.	1 600 A02 2V3
Battery 1 capacity	2 Ah
Battery voltage	12 V
Battery 1 weight	0.185 kg
Cell type	Li-Ion
Battery charging voltage	12 V
Charge current	4 A
Charge time at bat. cap.	24/35 min
2.0 Ah (80%/100%) approx.	
Charger weight	0.45 kg

MRP: ₹ 8,700

Suitable for charging of

- 12.0 V

Bosch tubular batteries

STARTER KITS

GAL 18V-40 + 2x GBA 18V 2.0Ah Professional



Technical Specifications

HSN code	85044030
Part no.	1 600 A02 2V4
Battery 1 capacity	2 Ah
Battery voltage	18 V
Battery 1 weight	0.35 kg
Cell type	Li-Ion
Battery charging voltage	14.4 – 18 V
Charge current	4 A
Charge time at bat. cap.	24/35 min
2.0 Ah (80%/100%) approx.	
Charger weight	0.55 kg

MRP: ₹ 14,600

Suitable for charging of

- 18.0 V

STARTER KITS

GAL 18V-40 + 2x GBA 18V 4.0Ah Professional



Technical Specifications

HSN code	85044030
Part no.	1 600 A02 2V2
Battery 1 capacity	4 Ah
Battery voltage	18 V
Battery 1 weight	0.6 kg
Cell type	Li-Ion
Battery charging voltage	14.4 – 18 V
Charge current	4 A
Charge time at bat. cap.	48/65 min
4.0 Ah (80%/100%) approx.	
Charger weight	0.55 kg

MRP: ₹ 20,150

Suitable for charging of

- 18.0 V

ProCORE 18V

MAXIMUM PERFORMANCE AND RUNTIME WITH FLEXIBLE POWER SYSTEM

Available in

THREE CLASSES

COMPACT



PERFORMANCE



ENDURANCE



FLEXIBLE POWER SYSTEM:

100% COMPATIBLE

WITH ALL BOSCH PROFESSIONAL 18 V TOOLS

87%


More Power

30%

Faster Material Removal

BOSCH HAMMER

DEMOLITION
HAMMERS



DEMOLITION HAMMER > 5 KG

GSH 500 Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 338 6F0
Input power	1,100 W
Impact rate at rated speed	2,900 bpm
Impact energy	7.8 J
Tool holder	17 Hex mm
Side handle	Straight handle
Weight	5.5 kg

Scope of supply:
Auxiliary handle;
1 Chisel; Carry case

MRP: ₹ 24,500



DEMOLITION HAMMER > 5 KG

GSH 500 MAX Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 338 7F0
Input power	1,100 W
Impact rate at rated speed	2,900 bpm
Impact energy	7.8 J
Tool holder	SDS MAX
Side handle	Straight handle
Weight	5.7 kg

Scope of supply:
Auxiliary handle;
1 Chisel; Carry case

MRP: ₹ 31,100



DEMOLITION HAMMER > 5 KG

GSH 5 Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 337 0F0
Rated power input	1,100 W
Impact energy	7.5 J
Rated speed	2,850 bpm
Weight without cable	5.6 kg

*with vario lock feature for chisel adjustment

Scope of supply:
Pointed chisel; Carry case;
Cleaning cloth; Grease tube;
Straight handle

MRP: ₹ 42,750



DEMOLITION HAMMER < 11 KG

GSH 11 E Promo Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 316 8F1
Power input	1,500 W
Impact rate	900 - 1,890 bpm
Impact energy	16.8 J
Weight	10.1 kg

Scope of supply:
Auxiliary handle; Carry case;
Grease tube; RTec pointed chisel;
Service kit

MRP: ₹ 54,500



DEMOLITION HAMMER > 11 KG

GSH 11 VC Professional

3



Technical Specifications

HSN code	84672100
Part no.	0 611 336 0F0
Power input	1,700 W
Impact energy	23 J
Impact rate at rated speed	900 - 1,700 bpm
Weight without cable	11.4 kg

Scope of supply:
Auxiliary handle; Carrying case;
Grease tube; Machine cloth;
Pointed chisel

MRP: ₹ 95,300



DEMOLITION HAMMER > 16 KG

GSH 16-30 Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 335 1F0
Power input	1,750 W
Impact rate	1,300 bpm
Impact energy	41 J
Weight	16.5 kg

Scope of supply:
Carrying handle; Trolley;
Grease tube; Machine cloth;
Pointed chisel

MRP: ₹ 1,33,600



DEMOLITION HAMMER > 27 KG

GSH 27 VC Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 30A 0F0
Rated power input	2,000 W
Impact energy	62 J
Impact rate at rated speed	1,000 bpm
Weight	29.5 kg

Scope of supply:
Paper box;
Plastic Bags

MRP: ₹ 2,65,100



DEMOLITION
HAMMERS





ROTARY HAMMER



ROTARY
HAMMERS

ROTARY HAMMER 1-2 KG



Technical Specifications

HSN code	84672100
Part no.	0 611 2A6 0F0
Rated input power	720 W
Impact energy	2 J
Impact rate at rated speed	0 – 4,800 bpm
Drilling diameter concrete, hammer drill bits	4 – 22 mm
Max. drilling diameter in (metal/wood/concrete)	13 / 30 / 22 mm
Tool holder	SDS plus
Scope of supply: Carrying case	MRP: ₹ 9,600

GBH 220 Professional



ROTARY HAMMER 1-2 KG




*Product available till stocks last

Technical Specifications

HSN code	84672100
Part no.	0 611 2A6 0F0
Rated input power	720 W
Impact energy	2 J
Impact rate at rated speed	0 – 4,800 bpm
Drilling diameter concrete, hammer drill bits	4 – 22 mm
Max. drilling diameter in (metal/wood/concrete)	13 / 30 / 22 mm
Tool holder	SDS plus
Scope of supply: 3 Drill bits; 1 Chisel	MRP: ₹ 10,500

GBH 220 Promo Professional



ROTARY HAMMER 1-2 KG



Technical Specifications

HSN code	84672100
Part no.	0 611 272 1F1
Power input	790 W
Impact energy	2.7 J
Drilling capacity	24 mm
No-load speed	1,300 rpm
Impact rate	4,200 bpm
Weight	2.8 kg

Scope of supply:
Carry case

MRP: ₹ 14,900

GBH 2-24 DRE Professional



ROTARY HAMMER 1-2 KG



Technical Specifications

HSN code	84672100
Part no.	0 611 251 755
Drilling diameter in concrete	4 - 26 mm
Drilling diameter in steel	13 mm
Drilling diameter in wood	30 mm
Core bits masonry	68 mm
Power input	800 W
No-load speed	0 - 900 rpm
Single impact energy	0 - 3 J
Weight	2.7 kg

Scope of supply:
Auxiliary handle; Depth gauge;
Carry case

MRP: ₹ 18,300

GBH 2-26 RE Professional



ROTARY HAMMER 1-2 KG

GBH 2-26 DRE + Drill Chuck Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 253 7F0
Drilling diameter in concrete	4 - 26 mm
Drilling diameter in steel	13 mm
Drilling diameter in wood	30 mm
Core bits masonry	68 mm
Power input	800 W
No-load speed	0 - 900 rpm
Single impact energy	2.7 J
Weight	2.7 kg

Scope of supply:
Auxiliary handle; Depth gauge;
Carry case

MRP: ₹ 19,800



ROTARY HAMMER 1-2 KG

GBH 2-28 DV Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 267 1F0
Drilling diameter in concrete	4 - 28 mm
Drilling diameter in steel	13 mm
Drilling diameter in wood	30 mm
Core dia. masonry	68 mm
Rated power input	850 W
No-load speed	0 - 1,300 rpm
Impact rate at rated speed	0 - 5,100 bpm
Impact energy	0 - 3.2 J
Weight	2.9 kg

Scope of supply:
Auxiliary handle; Depth gauge;
Carry case

MRP: ₹ 22,300



ROTARY HAMMER 4 KG

GBH 4-32 DFR Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 332 1F0
Drilling diameter in concrete	6 - 32 mm
Drilling diameter in steel	13 mm
Drilling diameter in wood	32 mm
Power input	900 W
No-load speed	0 - 800 rpm
Impact rate	0 - 3,600 bpm
Impact energy	4.2 J
Weight	4.7 kg

Scope of supply:
Auxiliary handle; Carry case;
Depth stop;
SDS-plus quick-change chuck

MRP: ₹ 43,100



ROTARY HAMMER 5 KG AND MORE

GBH 5-40 D Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 269 0F0
Drilling diameter in concrete	12 - 40 mm
Rated power input	1,100 W
Impact energy	8.5 J
Impact rate at rated speed	1,500 - 2,900 bpm
Rated speed	170 - 340 rpm
No-load speed	0 - 760 rpm
Weight	6.8 kg

Scope of supply:
Carrying cases; Cleaning cloth;
Grease tube; Auxiliary handle

MRP: ₹ 56,400



ROTARY HAMMER 8 KG

GBH 8-45 DV Professional



Technical Specifications

HSN code	84672100
Part no.	0 611 265 0F0
Rated power input	1,500 W
Impact energy	12.5 J
Impact rate at rated speed	1,380 - 2,760 bpm
Rated speed	0 - 305 rpm
Drilling diameter concrete, hammer drill bits	12 - 45 mm
Optimum range of applications in concrete with hammer drill bits	20 - 40 mm
Drilling diameter in concrete with breakthrough drill bits	80 mm
Weight without cable	8.9 kg



Scope of supply:
Grease tube; Cleaning cloth;
Carrying case

MRP: ₹ 1,02,200



ROTARY HAMMER 12 KG

GBH 12-52 DV Professional



Technical Specifications

HSN code	84672900
Part no.	0 611 266 0F0
Input power	1,700 W
Max. impact energy	19 J
Impact rate at rated speed	1,750 - 2,150 bpm
Rated speed	0 - 220 rpm
Drilling diameter in concrete with hammer drill bits	12 - 52 mm
Weight	11.9 kg



Scope of supply:
Carrying case, Grease tube;
Machine cloth;
Auxiliary handle

MRP: ₹ 1,22,200



DIAMOND/STONE CUTTER

DIAMOND
TECHNOLOGY



DIAMOND/STONE CUTTER

GDC 120 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 393 0F1
Rated power input	1,200 W
No-load speed	12,000 rpm
Tool blade	4 inch
Cutting depth (at 90°)	34 mm
Cord length	1.5 m
Net weight	2.5 kg



MRP: ₹ 5,500



DIAMOND/STONE CUTTER

GDC 121 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 393 1F1
Rated power input	1,250 W
No-load speed	12,000 rpm
Tool blade	5 inch
Depth of cut	40 mm
Cord length	1.5 m
Net weight	3 kg

*Product
available till
stocks last



MRP: ₹ 6,300



DIAMOND/STONE CUTTER

GDC 141 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 3A4 1F0
Rated power input	1,450 W
No-load speed	12,000 rpm
Max. cutting disc diameter	125 mm
Max. cutting depth	40 mm
Weight	3 kg



MRP: ₹ 6,550



SPECIALITY TOOLS



BLOWER



Technical Specifications

HSN code	84145920
Part no.	0 601 980 5F0
Power input	620 W
No-load speed	16,000 rpm
Volumetric flow rate	3.5 m³/min
Standard accessories	1 Nozzle
Weight without cable	1.7 kg

MRP: ₹ 4,300

GBL 620 Professional



BLOWER



Technical Specifications

HSN code	85081100
Part no.	0 601 980 4F5
Input power	820 W
No-load speed	16,000 rpm
Flow rate	4.5 m³/min
Weight	2.25 kg

Scope of supply:
50 mm nozzle,
Extension nozzle, Borehole
nozzle, Dust bag

MRP: ₹ 6,900

GBL 82-270 Professional



HEAT GUN



Technical Specifications

HSN code	84672900
Part no.	0 601 94D 0F0
Power input	1,800 W
Max temperature	60 / 350 / 550° C
Air flow rate	350 / 350 / 550 lpm
Over-heat protection	Yes
Weight	0.75 kg

Scope of supply:
Reducing nozzle

MRP: ₹ 3,700

GHG 180 Professional



HEAT GUN



Technical Specifications

HSN code	84672900
Part no.	0 601 2A6 2F0
Power input	2,000 W
Temperature range	50-630°C
Adjustable temperature steps	Yes
Air flow rate	150 - 500 litre/min
Durability	600 h
Weight	0.65 kg

Scope of supply:
Glass protection nozzle,
Surface nozzle, Welding glove,
Reduction nozzle,
Reflection nozzle

MRP: ₹ 10,500

GHG 20-63 Professional



HEAT GUN

GHG 20-60 Professional

6




Technical Specifications

HSN code	84672900
Part no.	0 601 2A6 4F0
Power input	2,000 W
Temperature max.	50-630°C
Adjustable temp steps	Yes
Air flow rate	~ 150 / 500 litre/min
Infinitely variable airflow control	No
Durability	500-750 h
Weight	0.55 kg

Scope of supply:
Glass protection nozzle

MRP: ₹ 11,900



METAL SURFACE FINISH

GPO 950 Professional




Technical Specifications

HSN code	84672900
Part no.	0 601 3A2 0F0
Power	950 W
Variable speed	600 - 2,100 rpm
Grinding spindle thread	M14
Stick pad diameter	ø165 mm
Max. accessory diameter	180 mm
Weight	2.3 kg

Scope of supply:
Sponge pad; Stick pad;
M14 & M16 adapter; Wrench;
Auxiliary handle; Auxiliary plate

MRP: ₹ 11,200



METAL SURFACE FINISH

GPO 12 CE (Promo) Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 389 0F1
No-load speed	750 - 3,000 rpm
Grinding spindle thread	M14
Rubber sanding plate	180 mm
Power input	1,250 W
Weight	2.5 kg

Scope of supply:
M14/M16 adapter;
Auxiliary handle; Spacer disc;
Auxiliary D-handle;
Wrench; Polishing pads

MRP: ₹ 17,900



RECIPSAW

GSA 120 Professional



Technical Specifications

HSN code	84672200
Part no.	0601 6B1 0F0
Power input	1,200 W
Stroke rate	0 - 3,000 per min.
Stroke length	29 mm
Blade change	SDS
Max. cutting depth in wood	220 mm
Max. cutting depth in metal	20 mm
Weight	3.7 kg

Scope of supply:
1 x reciprocating saw blade
S 1126 BEF, Allen key

MRP: ₹ 17,800



RECIPSAW



Technical Specifications

HSN code	85081100
Part no.	0 601 64E 2F0
Power input	1,300 W
Stroke rate at no load	0 - 2,900 spm
Stroke length	28 mm
Cutting depth in wood	220 mm
Cutting depth in metal	20 mm
Cutting depth in metal profiles and metal pipes	175 mm
Weight	1.1 kg

Scope of supply:

Carrying case;

1 x reciprocating saw blade S 2345 X; **MRP: ₹ 23,900**

1 x reciprocating saw blade S 123 XF

GSA 1300 PCE Professional



DRYWALL SANDER



Technical Specifications

HSN code	84672900
Part no.	0 601 7D4 0F0
Power input	550 W
No-load speed	340 - 910 rpm
Sanding pad diameter	215 mm
Sanding sheet diameter	225 mm
Weight	4.8 kg

Scope of supply:

Carry case; 1 x soft pad set;

1 x sanding sheet;

3 x cable clip

MRP: ₹ 34,850

New! GTR 550 Professional



VACUUM CLEANER



Technical Specifications

HSN code	85081100
Part no.	0 601 9E5 1F0
Power input	1,100 W
Container (gross/net)	15/8 L
Max. airflow	53 L/Sec
Max. vacuum pressure	270 mbar
Weight	6 kg

* Tool Socket for connecting Power Tools.

Scope of supply:

Crevice nozzle; Carton box;

3m anti-static hose; Elbow;

Tubes (2pcs); Plastic bags;

Floor nozzle set

MRP: ₹ 20,000

GAS 15 PS Professional



VACUUM CLEANER



Technical Specifications

HSN code	85081100
Part no.	0 601 97C 0F0
Power input	1,250 W
Vacuum pressure	200 mbar
Air Flow	63 L/Sec
Dust tank capacity gross	25 L
Tank capacity net dry/wet	21/16 L
Main filter class	H13 HEPA

Scope of supply:

3M Hose; Elbow; Crevice nozzle;

Floor nozzle set; Adapter;

Tubes (2 pcs);

Plastic bags (5 pcs)

MRP: ₹ 23,400

GAS 12-25 Professional



VACUUM CLEANER



Technical Specifications

HSN code	85081100
Part no.	0 601 9C3 0F0
Max. power input (Turbine)	1,380 W
Container volume, gross	35 L
Container volume, net	23 L
Container volume, net, water	19.2 L
Filter surface area	6,150 cm ²
Max. volume flow rate (Turbine)	74 L/sec
Max. vacuum pressure (Turbine)	254 mbar
Weight	11.6 kg
<i>Scope of supply:</i> Brown box; Hose with BIA nozzle 3 m, 35 mm diameter; Elbow; Crevice nozzle; Floor nozzle set; Disposal bag; Tool sleeve; SFC+ module	
MRP: ₹ 78,400	



*Tool Socket for connecting Power Tools.

VACUUM CLEANER



Technical Specifications

HSN code	85081100
Part no.	0 601 9C3 3F0
Max. power input (Turbine)	1,380 W
Container volume, gross	55 L
Container volume, net	43 L
Container volume, net, water	40 L
Filter surface area	6.150 cm ²
Max. volume flow rate (Turbine)	74 L/sec
Max. vacuum pressure (Turbine)	254 mbar
Weight	16.2 kg
<i>*Tool Socket for connecting Power Tools.</i> <i>Scope of supply:</i> 5 m anti-static hose; Elbow; Crevice nozzle; Floor nozzle set; Disposal bag; Tool sleeve	
MRP: ₹ 1,19,700	



OSCILLATING TOOL



Technical Specifications

HSN code	84672900
Part no.	0 601 237 0F0
Rated power input	300 W
No-load oscillation	8,000 - 20,000 opm
Oscillation angle on left and right	1.4°
Weight	1.5 kg

Scope of supply:
Carrying case; 1 set sanding sheet, Grit 2x80, Grit 2x120, Grit 1x240; Starlock BIM segment saw blade ACZ 85 EB, Wood & Metal; Starlock BIM plunge cut saw blade AIZ 32 APB, Wood & Metal, Curved-Tec; Starlock sanding plate AVZ 93 G Professional

MRP: ₹ 24,100

GOP 30-28 Professional





ROTARY & IMPACT DRILLS

7

DRILLS



ROTARY DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 1A9 5F1
Power input	350 W
No-load speed	0 - 2,800 rpm
Drilling capacity steel	10 mm
Drilling capacity wood	20 mm
Electronic switch	Yes
Reversible	Yes
Weight	1.2 kg


Scope of supply:
Keyed chuck 10 mm

MRP: ₹ 3,100

GBM 350 Professional



ROTARY DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 477 5F0
Power input	600 W
No-load speed	0 - 2,600 rpm
Chuck capacity	1.5 - 13 mm
Drilling diameter in steel	13 mm
Drilling diameter in aluminium	13 mm
Drilling diameter in wood	30 mm
Weight	1.7 kg

Scope of supply:
Keyed chuck 13 mm

MRP: ₹ 6,400

GBM 13 RE Professional



ROTARY DRILL



*Product
available till
stocks last



Technical Specifications

HSN code	84672100
Part no.	0 601 169 055
Power input	550 W
No-load speed	0 - 1,000/1,900 rpm
Chuck capacity	1 - 13 mm
Drilling diameter in steel	13/8 mm
Drilling diameter in aluminium	20/12 mm
Drilling diameter in wood	32/20 mm
Weight	1.9 kg

Scope of supply:
Auxiliary handle; Depth stop;
Keyed chuck

MRP: ₹ 12,600

GBM 13-2 Professional



ROTARY DRILL / STIRRER



Technical Specifications

HSN code	84672100
Part no.	0 601 1B0 0F1
Power input	850 W
No-load speed	0 - 630 rpm
Rated torque	11 Nm
Lock-on button	Yes
Stirrer capacity	160 mm
Wood drilling	40 mm
Metal drilling	16 mm
Weight	3 kg

Scope of supply:
Auxiliary handle

MRP: ₹ 15,100

GBM 1600 RE Professional



ROTARY DRILL

GBM 50-2 Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 1B4 0F0
Power input	1,200 W
No-load speed	50-255 / 100-510 rpm
Annular cutter	Ø 50 mm
Max. twist drill	Ø 23 mm
Max. thread	M16
Magnetic force	14,000 N
Weight	14.7 kg
Scope of supply: Carry case; MT2 drill drift; Hex key; Safety strap, Reduction sleeve; Pilot pin, Adapter for annular cutter, Cooling tank with hose; cooling tank holder	

MRP: ₹ 1,12,200



IMPACT DRILL

GSB 450 Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 216 1FK
Input power	450 W
Impact rate	0 - 41,600 bpm
No-load speed	0 - 2,600 rpm
Max. drill capacity: concrete	10 mm
Max. drill capacity: steel	8 mm
Max. drill capacity: wood	20 mm
Weight	1.5 kg

MRP: ₹ 3,700



IMPACT DRILL

GSB 450 Wrap Set Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 216 1FL
Input Power	450 W
Impact Rate	0 - 41,600 bpm
No-load speed	0 - 2,600 rpm
Max. drill capacity: concrete	10 mm
Max. drill capacity: steel	8 mm
Max. drill capacity: wood	20 mm
Weight	1.5 kg

Scope of supply:
4 Pcs Concrete Drill Bits, 4 Pcs Metal Drill Bits, 10 Pcs Screw-driver Bits, 4 Pcs Wood Drill Bits

MRP: ₹ 4,600



IMPACT DRILL

GSB 501 Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 216 1FD
Input power	500 W
Output power	250 W
No-load speed	0 - 2,600 rpm
Impact rate	0 - 25,700 bpm
Rated torque	1.5 Nm
Max. drill capacity: concrete	13 mm
Max. drill capacity: steel	10 mm
Max. drill capacity: wood	25 mm
Weight	1.5 kg

MRP: ₹ 4,200



IMPACT DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 217 1F3
Rated input power	600 W
No-load speed	0 - 2,800 rpm
Impact rate at no-load speed	0 - 44,800 bpm
Chuck capacity	13 mm
Weight	1.8 kg

Scope of supply:
Auxiliary handle; Depth gauge;
Keyed chuck 13 mm

MRP: ₹ 6,700

GSB 13 RE Professional



IMPACT DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 228 1F0
Rated input power	750 W
No-load speed	0 - 3,250 rpm
Chuck capacity	13 mm
Impact rate at no-load speed	0 - 48,500 bpm
Weight	1.8 kg

Scope of supply:
Auxiliary handle; Chuck key;
Depth gauge

MRP: ₹ 10,600

GSB 16 RE Professional



IMPACT DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 1A2 1F1
Power input	800 W
No-load speed (1 st /2 nd Gear)	1,100/3,000 rpm
Impact Rate	48,000 bpm
Max. drilling diameter (1 st /2 nd gear) Brickwork	20/16 mm
Steel	13/6 mm
Wood	40/25 mm
Weight	2.6 kg

Scope of supply:
Auxiliary handle; Chuck key;
Depth gauge

MRP: ₹ 16,100

GSB 20-2 RE Professional



IMPACT DRILL



Technical Specifications

HSN code	84672100
Part no.	0 601 216 1F4
Power input	500 W
No-load speed	0 - 2,600 rpm
Impact rate at no-load speed	0 - 41,600 bpm
Drilling diameter in masonry wall	10 mm
Drilling diameter in steel	8 mm
Drilling diameter in wood	20 mm
Chuck capacity	1 - 10 mm
Weight	1.5 kg

Scope of supply:
Keyed chuck 10 mm;
100 pcs accessory set

MRP: ₹ 6,900

GSB 10 RE Kit Professional



IMPACT DRILL


GSB 13 RE Kit Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 217 1F6
Power input	600 W
No-load speed	0 - 2,800 rpm
Impact rate	48,000 bpm
Drilling diameter in masonry	13 mm
Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Weight	1.6 kg

Scope of supply:
 Auxiliary handle; Depth gauge; **MRP: ₹ 8,800**
 Keyed chuck 13 mm;
 100 pcs accessory set



IMPACT DRILL

GSB 550 (XL Kit) Professional



Technical Specifications

HSN code	84672100
Part no.	0 601 1A1 5F3
Input power	550 W
Rated power input	0 - 2,800 rpm
Impact rate	0 - 41,800 bpm
Drilling capacity in concrete	13 mm
Drilling capacity steel/wood	10/25 mm

Scope of supply:
 5 x Masonry drill bits; 5 x Wood drill bits;
 8 x Hex keys; 10 x CRV bits 50 mm;
 18 x Sockets; 7 x Wrenches; **MRP: ₹ 8,700**
 Magnetic bit holder; Cutter; Hammer;
 Pliers; Long nose pliers; Adapter;
 Socket wrench; Screw set; Wall plug set





CHOPSAWS

CHOPSAWS



BENCH TOP CUT-OFF SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 B37 3F0
Input power	2,200 W
No-load speed	3,800 rpm
Disc diameter	355 mm
Cutting capacity rectangle	100 x 196 mm
Cutting capacity square	119 x 119 mm
Cutting capacity round	129 x 129 mm
Cutting capacity L-profile	130 x 130 mm
Weight	14 kg

Scope of supply:
Cutting disc

MRP: ₹ 16,400

GCO 220 Professional



BENCH TOP CUT-OFF SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 B37 1F0
Input power	2,400 W
Cutting capacity rectangle	100 x 196 mm
Cutting capacity square	119 x 119 mm
Cutting capacity L-profile	130 x 130 mm
No-load speed	3,800 rpm
Disc diameter	355 mm
Weight	17.5 kg

Scope of supply:
Cutting disc

MRP: ₹ 20,000

GCO 14-24 Professional



BENCH TOP CUT-OFF SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 B37 2F0
Rated power input	2,400 W
No-load speed	3,800 rpm
Saw blade diameter	355 mm
Saw blade bore	25.4 mm
Cutting capacity at rectangle	100 x 196 mm
Cutting capacity at square	119 x 119 mm
Cutting capacity at L-profile	130 x 130 mm
Weight	18.1 kg

Scope of supply:
Cutting disc

MRP: ₹ 21,600

GCO 14-24 J (Soft-Start) Professional



METALWORKING



STRAIGHT GRINDER

GGG 3000 L Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 224 0F0
Power input	300 W
No-load speed	0 - 28,000 rpm
Collet chuck diameter max.	8 mm
Spindle collar diameter	41 mm
Weight without cable	1.5 kg

Scope of supply:
Collet chuck; Lock nut;
Spanner

MRP: ₹ 10,300



STRAIGHT GRINDER

GGG 5000 L Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 224 1F0
Power input	500 W
No-load speed	33,000 rpm
Collet chuck diameter max.	8 mm
Spindle collar diameter	41 mm
Weight without cable	1.4 kg

Scope of supply:
Collet chuck;
2 x Single head open
end wrench

MRP: ₹ 12,400



STRAIGHT GRINDER

GGG 28 LCE Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 221 1F0
Power input	650 W
No-load speed	10,000 - 28,000 rpm
Tool holder	Up to 8 mm
Weight without cable	1.6 kg

Scope of supply:
Clamping unit;
13 mm spanner;
19 mm spanner

MRP: ₹ 27,900



BT GRINDERS

GBG 35-15 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 27A 3F0
Power input	350 W
No load speed	3,000 rpm
Disc diameter	150 mm
Grinding disc width	20 mm
Grinding disc bore	20 mm
Weight	10 kg

Scope of supply:
Grinding wheel, Normal grit, Grit 24;
Grinding wheel, Normal grit, Grit 60

MRP: ₹ 13,000



BT GRINDERS



Technical Specifications

HSN code	84672900
Part no.	0 601 27A 4F0
Power input	600 W
No load speed (50/60Hz)	3,000 rpm
Disc diameter	200 mm
Grinding disc width	25 mm
Grinding disc bore	32 mm
Weight	17 kg

Scope of supply:

Grinding wheel, Normal grit, Grit 24;
Grinding wheel, Normal grit, Grit 60

MRP: ₹ 20,700

GBG 60-20 Professional



IMPACT WRENCH



Technical Specifications

HSN code	84672100
Part no.	0 601 444 0F0
Power input	500 W
Torque max. (hard/soft)	250/160 Nm
Rated speed	500 - 1,300 rpm
Tool holder	1/2" Sq. Drive
Bolt diameter	Max. M18
Weight without cable	3.2 kg

MRP: ₹ 62,400

GDS 18 E Professional



IMPACT WRENCH



Technical Specifications

HSN code	84672100
Part no.	0 601 435 1F3
Power input	920 W
Torque max. (hard/soft)	1,000 / 500 Nm
Rated speed	860 rpm
Tool holder	1" Sq. Drive
Bolt diameter	Max. M30
Weight	7.3 kg

Scope of supply:

Auxiliary handle;
Hanging loop

MRP: ₹ 1,34,600

GDS 30 Professional





ANGLE GRINDERS



SMALL ANGLE GRINDER 4"

GWS 600 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 375 05F
Power input	670 W
No-load speed	11,000 rpm
Grinding spindle thread	M 10
Disc diameter	100 mm
Weight	1.8 kg

Scope of supply:
Auxiliary handle; Guard;
Round nut; Pin spanner;
Clamping flange

MRP: ₹ 3,600



SMALL ANGLE GRINDER 4"

GWS 750-100 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 394 0F0
Power input	750 W
Disc diameter	100 mm
No-load speed	11,000 rpm
Spindle diameter	M 10
Weight	1.8 kg

Scope of supply:
Auxiliary handle; Guard;
Round nut; Pin spanner;
Clamping flange

MRP: ₹ 4,900



SMALL ANGLE GRINDER 4"

GWS 900-100 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 396 0F0
Rated power input	900 W
Disc diameter	100 mm
No-load speed	11,000 rpm
Spindle diameter	M 10
Weight	1.8 kg

Scope of supply:
Wrench; Protective guard;
Auxiliary handle

MRP: ₹ 6,000



SMALL ANGLE GRINDER 5"

GWS 6-125 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 375 15A
Rated power input	670 W
No-load speed	11,000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Weight without cable	1.9 kg

Scope of supply:
Auxiliary handle; Guard;
Round nut; Pin spanner;
Clamping flange

MRP: ₹ 5,300



SMALL ANGLE GRINDER 5"

GWS 900-125 S Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 396 1F2
Rated input power	900 W
No-load speed	2,800 - 11,000 rpm
Disc diameter	125 mm
Grinding spindle thread	M 14
Weight	1.9 kg


Scope of supply:
Wrench;
Protective guard;
Auxiliary handle

MRP: ₹ 7,800



SMALL ANGLE GRINDER 5"

GWS 14-125 CI Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 824 2F1
Power input	1,400 W
No-load speed	11,000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Weight without cable	2.2 kg

Scope of supply:
Auxiliary handle; Guard;
Round nut; Pin spanner;
Clamping flange

MRP: ₹ 11,300



SMALL ANGLE GRINDER 5"

GWS 18-125 L Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 7A3 0F1
Power input	1,800 W
No-load speed	11,500 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Weight without cable	2.5 kg

Scope of supply:
Wrench; Protective guard;
Auxiliary handle

MRP: ₹ 17,570



ANGLE GRINDER with X-LOCK

GWX 17-125 S Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 7C4 0F2
Power input	1,700 W
No-load speed	2,800 - 11,500 rpm
Disc diameter	125 mm
Wire cup brush, diameter	75 mm
Weight	2.5 kg

Scope of supply:
Wrench; Protective guard;
Auxiliary handle

MRP: ₹ 20,100



SMALL ANGLE GRINDER - CONCRETE

GBR 15 CAG Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 776 0F0

Rated power input 1,500 W

No-load speed 9,300 rpm

Grinding spindle thread M 14

Grinding head, diameter 125 mm

Weight 2.6 kg

*Tool comes with 1 No. Bosch Concrete grinding wheel

Scope of supply:

Clamp key; Carry case;

Diamond grinding head;

3 x replacement brush rings

MRP: ₹ 73,600



LARGE ANGLE GRINDER 7"

GWS 2000-180 Professional



*Product available till stock last



Technical Specifications

HSN code 84672900

Part no. 0 601 8B7 0F0

Power input 2,000 W

No-load speed 8,500 rpm

Grinding spindle thread M 14

Disc diameter 180 mm

Weight without cable 5.3 kg

Scope of supply:

Auxiliary handle; Guard;

Round nut; Pin spanner;

Clamping flange

MRP: ₹ 11,000



LARGE ANGLE GRINDER 7"

GWS 2200-180 Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 8C0 0F0

Rated power input 2,200 W

No-Load speed 8,500 rpm

Grinding spindle M 14

Disc diameter 180 mm

Weight 5.5 kg


Scope of supply:

Auxiliary handle; Guard;

Round nut; Pin spanner;

Clamping flange

MRP: ₹ 12,100



LARGE ANGLE GRINDER 7"

New! GWS 24-180 Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 8C2 0F0

Power input 2,400 W

No-load speed 8,500 rpm

Grinding spindle thread M 14

Disc diameter 180 mm

Weight without cable 4.9 kg

Scope of supply:

Auxiliary handle; Guard;

Round nut; Pin spanner;


Clamping flange

MRP: ₹ 15,155



CYCLON TECH

CYCLON
— TECH —



RESTART PROTECTION

Prevents accidental restarts

OVERLOAD PROTECTION

Prevents motor burnout

Under extended overload conditions

LARGE ANGLE GRINDER 7"

New! GWS 24-180 JZ Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 8C2 3F0

Power input 2,400 W

No-load speed 8,500 rpm

Disc diameter 180 mm

Grinding spindle thread M14

Weight 5.8 kg

Scope of supply:

Two-hole spanner; Backing flange;

Locking nut; Cardboard box;

Protective cover;

Auxiliary handle

MRP: ₹ 16,690



LARGE ANGLE GRINDER 7"

GWS 26-180 H Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 855 1F0

Rated power input 2,600 W

No-load speed 8,500 rpm

Grinding spindle thread M 14

Disc diameter 180 mm

Scope of supply:

Auxiliary handle; Guard;

Round nut; Pin spanner;

Clamping flange

MRP: ₹ 26,500



LARGE ANGLE GRINDER 9"

GWS 2200-230 Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 8C0 1F0

Rated power input 2,200 W

No-Load speed 6,500 rpm

Grinding spindle M 14

Disc diameter 230 mm

Weight 5.5 kg

Scope of supply:

Auxiliary handle; Guard;

Round nut; Pin spanner;

Clamping flange

MRP: ₹ 26,900



LARGE ANGLE GRINDER 9"

New! GWS 24-230 H Professional



Technical Specifications

HSN code 84672900

Part no. 0 601 854 455

Power input 2,400 W

No-load speed 6,500 rpm

Grinding spindle thread M 14

Disc diameter 230 mm

Weight without cable 6 kg

Scope of supply:

Auxiliary Handle; Guard;

Round nut; Pin Spanner;

Clamping Flange

MRP: ₹ 16,690



LARGE ANGLE GRINDER 9"

New! GWS 24-230 JZ Professional

Technical Specifications

HSN code	84672900
Part no.	0 601 8C3 3F0
Power input	2,400 W
No-load speed	6,500 rpm
Grinding spindle thread	M 14
Disc diameter	230 mm
Weight	6 KG

Scope of supply:
Two-hole spanner; Backing flange;
Locking nut; Cardboard box;
Protective cover;
Auxiliary handle

MRP: ₹ 17,845



LARGE ANGLE GRINDER 9"

GWS 26-230 H Professional

Technical Specifications

HSN code	84672900
Part no.	0 601 856 1F0
Power input	2,600 W
No-load speed	6,500 rpm
Grinding spindle thread	M 14
Disc diameter	230 mm
Weight without cable	5.2 kg

Scope of supply:
Auxiliary Handle; Guard;
Round nut; Pin Spanner;
Clamping Flange

MRP: ₹ 26,900





WOODWORKING



CIRCULAR SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 6B3 0F0
Power input	1,400 W
Blad diameter/bore size	184 / 20 mm
No-load speed	6,000 rpm
Max. depth of cut at 0°	64 +/-1
Cutting depth at 90°	64 mm
Cutting depth at 45°	45 mm

Scope of supply:
Parallel guide;
Circular saw blade
Allen key

MRP: ₹ 10,500



CIRCULAR SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 623 0F1
Power input	1,400 W
No-load speed	5,500 rpm
Saw blade bore	20 mm
Saw blade diameter	184 mm
Cutting depth (90°)	67 mm
Cutting depth (45°)	48 mm
Weight without cable	4.1 kg

Scope of supply:
Allen key WAF 5; Parallel guide;
Saw blade

MRP: ₹ 14,400



CIRCULAR SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 5A2 0F0
Power input	2,050 W
No-load speed	0 - 5,300 rpm
Saw blade bore	25 mm
Saw blade diameter	235 mm
Cutting depth (90°)	85 mm
Cutting depth (45°)	65 mm
Weight without cable	7.6 kg

Scope of supply:
Allen key; Wrench;
Saw blades

MRP: ₹ 18,700



GKS 235 Turbo Professional

JIGSAW



Technical Specifications

HSN code	84672200
Part no.	0 601 5A8 0F0
Power input	450 W
No-load speed	800 - 3,100 rpm
Max. cutting depth in wood	65 mm
Max. cutting depth in aluminium	10 mm
Max. cutting depth in metal	3 mm
Weight	1.9 kg

Scope of supply:
1 Wood blade; 1 Allen key

MRP: ₹ 5,600



GST 650 Professional

JIGSAW

GST 700 Professional



*Product available till stocks last



Technical Specifications

HSN code	84672200
Part no	0 601 2A7 0F1
Power input	500 W
Stroke rate	1,450 - 3,200 spm
Cutting depth in wood	70 mm
Stroke length	20 mm
Weight	2.1 kgs.

Scope of supply:
Wood blade T111C; Softbag;
1 hex key; Dust Cover;
3 Foam

MRP: ₹ 9,110



JIGSAW

GST 90 BE Professional



Technical Specifications

HSN code	84672200
Part no.	0 601 58F 0F0
Power input	650 W
No-load stroke rate	500 - 3,100 spm
Cable length	2.5 m
Cutting depth in wood	90 mm
Cutting depth in aluminium	20 mm
Cutting depth in non-alloyed steel	10 mm
Weight	2.6 kg

Scope of supply:
Dust extraction set; Carry case; MRP: ₹ 19,100
Hex key WAF 5; Anti-splinter guard;
5 x jigsaw blade T 144 D



JIGSAW

GST 150 BCE Professional



Technical Specifications

HSN code	84672200
Part no.	0 601 513 0F0
Power input	780 W
No-load stroke rate	500 - 3,100 spm
Cable length	4 m
Stroke height	26 mm
Cutting depth in wood	150 mm
Cutting depth in aluminium	20 mm
Cutting depth in non-alloyed steel	10 mm
Weight without cable	2.7 kg

Scope of supply:
Dust extraction set; Anti-splinter guard; MRP: ₹ 25,600
Carry case; Glide shoe; 3 x saw blades



TABLE SAW

New! GTS 254 Professional



Technical Specifications


HSN code	84672200
Part no.	0 601 B45 0F0
Cutting depth 0"/45"	80 / 55 mm
Rip cut capacity	545 mm
Power	1,800 / 15A
Saw blade diameter	254 mm
Overload / restart protection	Yes
Table size	555 x 555 mm
Weight with stand	24.4 kg

Scope of supply:
Wood disc; Metal stand

MRP: ₹ 35,600



TABLE SAW



Technical Specifications

HSN code	84672200
Part no.	0 601 B30 5F0
No-load speed	3,650 rpm
Table size	642 x 634 mm
Saw blade diameter	254 mm
Cutting height 90°	79 mm
Saw bore diameter	30 mm
Max. cutting on right	635 mm
Max. cutting on left	255 mm
Weight	27 kg

Scope of supply:
Angle guide;
Dust extraction adapter;
Parallel guide; Push stick;
Saw blade 254 x 30 mm

MRP: ₹ 97,800

GTS 10 J Professional



MITRE SAW



*Without Blade



Technical Specifications

HSN code	84672200
Part no.	0 601 B29 0F0
Power input	1,700 W
Cutting capacity, 0°	89 mm
Cutting capacity, 45° incline	67 mm
No-load speed	4,800 rpm
Saw blade diameter	255 mm
Saw blade bore	25.4 mm
Weight	14.1 kg

Scope of supply:
Allen key; Pro-Prevnes;
Wrench; Carton box

MRP: ₹ 30,500

GCM 10 MX Professional



PLANER



Technical Specifications

HSN code	84672900
Part no.	0 601 596 0F0
Power input	650 W
No-load speed	16,500 rpm
Planing width	82 mm
Max. cutting depth	2.6 mm
Weight	2.8 kg

Scope of supply:
Allen key; Parallel guide;
Sharpening device for HSS blade;
Setting gauge for HSS blade

MRP: ₹ 10,500

GH0 6500 Professional



PLANER




Technical Specifications

HSN code	84672900
Part no.	0 601 594 0F1
Power input	710 W
Adjustable rebating depth	0 - 9 mm
No-load speed	16,500 rpm
Cutting width	82 mm
Cutting depth max.	1 mm
Weight without cable	2.5 kg

Scope of supply:
Guide bracket;
Single-ended open-jaw spanner;
Stop bracket

MRP: ₹ 11,600

GH0 10-82 Professional



PLANER

GHO 26-82 D Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 5A4 0F0
Power input	710 W
No-load speed	16,500 rpm
Recess	9 mm
Cutting width	82 mm
Max. cutting depth	2.6 mm
Weight	3 kg

Scope of supply:
Dust box; Parallel guide;
Auxiliary blade

MRP: ₹ 14,600



RANDOM ORBIT SANDER

GEX 125-1 AE Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 387 5F2
Power input	250 W
Sanding pad diameter	125 mm
No-load speed	7,500 - 12,000 rpm
Orbital stroke rate	15,000 - 24,000 opm
Eccentricity	1.25 mm
Oscillating circuit diameter	2.5 mm
Weight	1.3 kg

Scope of supply:
Dust box; Sanding disc

MRP: ₹ 9,600



RANDOM ORBIT SANDER

GEX 34-150 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 372 8F0
Power input	340 W
No-load speed	4,500 - 12,000 rpm
Orbital stroke rate	9,000 - 24,000 opm
Orbit diameter	4 mm
Pad diameter	150 mm
Cord	4 mm
Weight	2.4 Kg

Scope of supply:
Vac Adapter, Dust bag,
Medium Pad 150mm.

MRP: ₹ 20,200



ORBITAL SANDER

GSS 140 Professional



Technical Specifications

HSN code	84672900
Part no.	0 601 2A8 0F0
Power input	220 W
No-load speed	14,000 rpm
No-load orbital stroke rate	28,000 opm
Orbital diameter	1.5 mm
Sanding sheet dimension	114 x 140 mm
Sanding plate dimension	101 x 112 mm
Weight	1.2 kg

Scope of supply:
Wood Sanding paper 3 pcs

MRP: ₹ 4,300



ORBITAL SANDER



Technical Specifications

HSN code	84672900
Part no.	0 601 298 0F0
Power input	190 W
No-load speed	12,000 rpm
Sanding sheet size	230 mm x 93 mm
Sanding plate size	182 mm x 92 mm
Weight	1.5 kg

Scope of supply:
Carton box;
3 Sanding sheets

MRP: ₹ 8,100

GSS 2300 Professional



ROUTER



Technical Specifications

HSN code	84672900
Part no.	0 601 6A0 0F0
Power input	550 W
No-load speed	33,000 rpm
Bit size	6 1/4" mm
Weight	1.4 kg

Scope of supply:
Parallel guide; Roller guide;
Template guide; Spinners;
Straight bit

MRP: ₹ 7,700

GKF 550 Professional



ROUTER



Technical Specifications

HSN code	84672900
Part no.	0 601 6B7 0F0
Power input	1,300 W
No-load speed	11,000 - 28,000 rpm
Bit holder	6 - 8.0 mm
Router bit diameter	40 mm
Weight	3.5 kg

Scope of supply:
Wrench; Parallel guide; Template
guide; Dust extraction adapter;
Centering pin; Guide roller,
Collet 8 mm; Collet 6 mm

MRP: ₹ 13,900

GOF 130 Professional



DRYWALL SCREWDRIVER



Technical Specifications

HSN code	84672900
Part no.	0 601 4A2 0F0
Power input	650 W
No-load speed	0 - 5,000 rpm
Torque, max.	12 Nm
Bit holder	1/4" internal hexagon
Weight	1.4 kg

Scope of supply:
Carry case

MRP: ₹ 11,600

GTB 650 Professional





**STORAGE
SOLUTIONS**

STORAGE BOXES

i-BOXX 53



Technical Specifications

HSN code	39231090
Part number	1 600 A00 1RV
Material	Plastic
Application	For use with L-Boxx 3D
Weight	0.81 kg

Scope of supply:
Thin drawer for L-BOXX-3D

MRP: ₹ 2,700



STORAGE BOXES

i-BOXX 72




Technical Specifications

HSN code	39231090
Part number	1 600 A00 1RW
Material	Plastic
Application	For use with L-Boxx-3D
Weight	0.87 kg

Scope of supply:
Thin drawer for L-BOXX-3D

MRP: ₹ 2,100



STORAGE BOXES

L-BOXX 102 Professional



Technical Specifications

HSN code	39231090
Part number	1 600 A01 2FZ
Material	ABS
Suitable for	All types of Power Tools
Weight	1.8 kg



MRP: ₹ 3,700



STORAGE BOXES

L-BOXX 136 Professional



Technical Specifications

HSN code	39231090
Part number	1 600 A01 2G0
Material	ABS
Application	For use with L-Boxx-3D
Weight	2.2 kg

MRP: ₹ 3,800



L-BOXX 238 Professional



HSN code	39231090
Part number	1 600 A01 2G2
Material	ABS
Weight	2.8 kg

MRP: ₹ 5,200




L-BOXX 374 Professional



HSN code	39231090
Part number	1 600 A01 2G3
Material	ABS
Suitable for	All types of Power Tools
Weight	3.0 kg

MRP: ₹ 6,900



STORAGE BOXES

L-BOXX Mini Professional



HSN code	39231090
Part number	1 600 A00 7SF
Material	PP
Maximum load	1.5 kg
Weight	0.3 kg

MRP: ₹ 1,200




STORAGE BOXES

L-BOXX 306 Professional



HSN code	39231090
Part number	1 600 A00 1RU
Material	ABS
Product Type	LS-BOXX Tool Storage
Weight	3.85 kg

MRP: ₹ 8,700



STORAGE BOXES

LT-BOXX 170 Professional



Technical Specifications

HSN code	39231090
Part number	1 600 A00 222
Material	ABS
Weight	2.3 kg

MRP: ₹ 5,900



STORAGE BOXES

LT-BOXX 272 Professional



Technical Specifications

HSN code	39231090
Part number	1 600 A00 223
Material	ABS

MRP: ₹ 7,570



TOOL BAG

MEDIUM TOOL BAG - 48 x 28 x 30



Technical Specifications

HSN code	39231090
Part number	1 600 A00 3BJ
Length	480 mm
Width	300 mm
Height	280 mm
Weight	1.5 kg

MRP: ₹ 3,200



TOOL BAG

LARGE TOOL BAG - 55 x 35 x 35



Technical Specifications

HSN code	39231090
Part number	1 600 A00 3BK
Length	550 mm
Width	350 mm
Height	350 mm

MRP: ₹ 3,700



Symbols and their meaning.



Guide Rail
For precise cuts.



"Plus-clean" System
Electromagnetic filter cleaning for clean filter surfaces and lasting suction power.



Removable Cable



Handle



Carrying Case



Slim Grip
Slim Grip



Spindle Lock
Faster, easier disc tool changing.



High Torque



Adjustable Cutter Clearance
Screw to adjust the cutter clearance according to sheet thickness.



L-BOXX
Intelligent system for transport and storage.



2 in 1 Dual Tool Holder
Easily switch between screwdriving and bolting applications



Bosch SDS System
Fast, tool-free changing of application tools.



Bosch SDS-pro System
For fast, tool-free changing of grinding discs.



SDS-plus Tool Holder
Optimum power transfer. For Rotary Hammers in the 2Kg; 4kg class.



SDS-max Tool Holder
Optimum power transfer. For Rotary Hammers and Demolition Hammers from the 5kg class onwards.



Electronic
Speed preselection for adjusting to suit any application.



Constant Electronic
Power booster for heavy loads. Constant speed, even under load.



Torque Control
Torque preselection for uniform screwdriving of a large number of screws.



Anti-Rotation
Interruption of power transfer.



Overload Clutch



Forward/Reverse Rotation
For inserting and removing screws.



Lithium-ion Technology
No self-discharge. No memory effect.



Anti-rotation Protective Guard
Stands firm, even if the disc breaks.



Brake System
The brake reduces the run-out time of the disc by up to 80%.



Kick-Back Stop
More protection: the tool shuts down when jammed.



Restart Protection
Prevents the tool from automatically starting up after a power cut.



Dust Extraction
Directly into the integral dust bag on the machine and/or using an all-purpose dust extractor.



Direct Cooling
For high overload capability and a long service life.



Starting Current Limitation
For a safe start.



Saw Blade Pendulum Action
Adjustable 3-stage or 4-stage saw blade pendulum action.



INOX
For a perfect finish on stainless steel



Easy-Fit
A perfect fit for paper with hook and loop fastening and for rolls of paper.



Fine Depth Adjustment
Scale accurate to 1/10 mm for precise routing work.



Turbo Blower
Blower for optimum view of the cutting line.



Double Insulation



Speed



Light Weight



Auto-Lock
For fastest possible tool changes with one hand.



Turbo Power
More power for faster working.



Woodrazor
Extremely sharp blades and an exact fit.



Laser Class 3R
Laser class for various measuring tools.



Laser Class 2
Laser class for measuring tools.



Bosch Wood Protection System
For preventing damage.



Bosch Full Force Technology
For eliminating wasted power and space.



Vibration Control
Patented vibration damping system.

Part Number	Category	Model Number	HSN Code	MRP ₹
-------------	----------	--------------	----------	-------

CORDLESS

06019H21L1	Screwdriver	Bosch GO 2.0	84672100	4,900
06019H2181	Screwdriver	Bosch GO 2.0 Kit	84672100	5,300
06019G80F1	Drill Driver	GSR 120-Li (Single Battery)	84672100	6,800
06019G80F0	Drill Driver	GSR 120 Li	84672100	10,900
06019G9082	Drill Driver	GSR 12V-30 (Solo)	84672100	9,500
0 601 9J9 180	Drill Driver	GSR 12V-35 HX (Solo)	84672100	10,800
06019F60F0	Drill Driver	GSR 12V-15 FC	84672100	24,500
06019F81F0	Drill Driver	GSR 180-Li	84672100	16,900
0 601 9H5 082	Drill Driver	GSR 18V-50 Solo	84672100	12,950
0 601 9H5 0F0	Drill Driver	GSR 18V-50 Kit	84672100	24,480
0 601 9G8 1F2	Impact Drill Driver	GSB 120 Li Kit	84672100	11,856
0 601 9F8 3F0	Impact Drill Driver	GSB 180-Li	84672100	17,800
0 601 9H5 0F0	Drill Driver	New! GSB 18V-150 C (Solo)	84672100	27,000
06019F00F0	Impact Wrench	GDR 120 Li	84672100	15,000
06019E00F6	Impact Wrench	GDR 12 V-EC	84672100	24,800
0 601 9G5 1F0	Impact Wrench	New! GDR 180 Li	84672100	26,400
0 601 9G4 2F0	Impact Wrench	GDX 18V-200 C	84672100	35,650
06019J23F0	Impact Wrench	GDS 18V-200	84672100	31,000
0 601 9G6 1F0	Impact Wrench	GDS 250 Li	84672100	31,200
06019K00F0	Impact Wrench	GDS 18V-400	84672100	42,750
06019J85F0	Impact Wrench	GDS 18V-1050 H	84672900	57,700
06119111F0	Rotary Hammers 1-2 Kg	GBH 180-Li (Brushless)	84672900	38,100
0611914082	Rotary Hammers 4 Kg	GBH 18V-34 (Solo)	84672900	72,850
06019J40F0	Small Angle Grinder	GWS 18V-10 (100 mm) Kit	84672900	41,200
06019H90F0	Small Angle Grinder	GWS 180 Li	84672900	34,100
0 601 9H9 0K0	Small Angle Grinder	GWS 180 Li (Solo)	84672900	14,450
06019J4002	Small Angle Grinder	GWS 18V-10 (125 mm) (Solo)	84672900	18,850
0 601 9F5 1L0	Blower	GBL 18V-120 (Solo)	84672900	8,550
0 601 9K1 0F1	Cutting	New! Pro Pruner	84672900	20,720
0 601 6A2 2L0	Circular Saws	GKS 18V-57 (Solo)	84672900	21,200
0 601 6A5 080	All Purpose / Recipsaw	GSA 18V-Li Compact (Solo)	84672900	24,600
0 601 6A8 108	All Purpose / Recipsaw	GSA 18V-32 (Solo)	84672900	56,650

BATTERY

1600A00F6X	Battery	GBA 12V 2.0 Ah	85076000	3,400
1600A001CG	Battery	GBA 18V 2.0 Ah	85076000	5,500
1600A00163	Battery	GBA 18V 4.0 Ah	85076000	8,300
1600A0193L	Battery	ProCORE 18V 4.0 Ah	85076000	10,500
1600A0193N	Battery	ProCORE 18V 8.0 Ah	85076000	19,500
1600A022V0	Charger	GAL 12V-40	85044030	3,100
1600A022V1	Charger	GAL 18V-40	85044030	4,000
1 600 A02 2V3	Starter Kits	GAL 12V-40 + 2x GBA 12V 2.0Ah	85044030	8,700
1 600 A02 2V4	Starter Kits	GAL 18V-40 + 2x GBA 18V 2.0Ah	85044030	14,600
1 600 A02 2V2	Starter Kits	GAL 18V-40 + 2x GBA 18V 4.0Ah	85044030	20,150

DEMOLITION HAMMERS

06113386F0	Demolition Hammer < 5 Kg	GSH 500	84672100	24,500
06113387F0	Demolition Hammer < 5 Kg	GSH 500 MAX	84672100	31,100
06113370F0	Demolition Hammer < 5 Kg	GSH 5	84672100	42,750
06113168F1	Demolition Hammer < 11 Kg	GSH 11 E Promo	84672100	54,500
06113360F0	Demolition Hammer < 11 Kg	GSH 11 VC	84672100	95,300
06113351F0	Demolition Hammer > 16 Kg	GSH 16-30	84672100	1,33,600
061130A0F0	Demolition Hammer > 27 Kg	GSH 27 VC	84672100	2,65,100

Part Number	Category	Model Number	HSN Code	MRP ₹
ROTARY HAMMERS				
06112A60F0	Rotary Hammer 1 - 2 Kg	GBH 220	84672100	9,600
06112A60F0	Rotary Hammer 1 - 2 Kg	GBH 220 Promo	84672100	10,500
06112721F1	Rotary Hammer 1 - 2 Kg	GBH 2-24 DRE	84672100	14,900
0611251755	Rotary Hammer 1 - 2 Kg	GBH 2-26 RE	84672100	18,300
06112537F0	Rotary Hammers 1 - 2 Kg	GBH 2-26 DRE + Drill Chuck	84672100	19,800
06112671F0	Rotary Hammers 1 - 2 Kg	GBH 2-28 DV	84672100	22,300
06113321F0	Rotary Hammers 4 Kg	GBH 4-32 DFR	84672100	43,100
06112690F0	Rotary Hammer 5 Kg and more	GBH 5-40 D	84672100	56,400
06112650F0	Rotary Hammer 5 Kg	GBH 8-45 DV	84672100	1,02,200
06112660F0	Rotary Hammers 12 Kg	GBH 12-52 DV	84672900	1,22,200
DIAMOND TECHNOLOGY				
06013930F1	Stone Cutter	GDC 120	84672900	5,500
06013931F1	Stone Cutter	GDC 121	84672900	6,300
06013A41F0	Stone Cutter	GDC 141	84672900	6,550
SPECIALITY TOOLS				
06019805F0	Blower	GBL 620	84145920	4,300
06019804F5	Blower	GBL 82-270	85081100	6,900
060194D0F0	Heat Gun	GHG 180	84672900	3,700
06012A62F0	Heat Gun	GHG 20-63	84672900	10,500
06012A64F0	Heat Gun	GHG 20-60	84672900	11,900
06013A20F0	Metal Surface Finish	GPO 950	84672900	11,200
06013890F1	Metal Surface Finish	GPO 12 CE (Promo)	84672900	17,900
06016B11F0	Recipsaw	GSA 120	84672200	17,800
060164E2F0	Recipsaw	GSA 1300 PCE	85081100	23,900
0 601 7D4 0F0	DRYWALL SANDER	New! GTR 550	85081100	34,850
06019E51F0	Vacuum Cleaner	GAS 15 PS	85081100	20,000
060197C0F0	Vacuum Cleaner	GAS 12-25	85081100	23,400
06019C30F0	Vacuum Cleaner	GAS 35 L SFC	85081100	78,400
06019C33F0	Vacuum Cleaner	GAS 55 M AFC	85081100	1,19,700
06012370F0	Oscillating Tools	GOP 30-28	84672900	24,100
DRILLS				
06011A95F1	Rotary Drill	GBM 350	84672100	3,100
06014775F0	Rotary Drill	GBM 13 RE	84672100	6,400
0601169055	Rotary Drill	GBM 13-2	84672100	12,600
06011B00F1	Rotary Drill	GBM 1600 RE	84672100	15,100
06011B40F0	Rotary Drill	GBM 50-2	84672100	1,12,200
06012161FK	Impact Drill	GSB 450	84672100	3,700
06012161FL	Impact Drill	GSB 450 Wrap Set	84672100	4,600
06012161FD	Impact Drill	GSB 501	84672100	4,200
06012171F3	Impact Drill	GSB 13 RE	84672100	6,700
06012281F0	Impact Drill	GSB 16 RE	84672100	10,600
06011A21F1	Impact Drill	GSB 20-2 RE	84672100	16,100
06012161F4	Impact Drill	GSB 10 RE Kit	84672100	6,900
06012171F6	Impact Drill	GSB 13 RE Kit	84672100	8,800
06011A15F3	Impact Drill	GSB 550 (XL Kit)	84672100	8,700
CHOPSAWS				
0601B373F0	Bench Top Cut-off Saw	GCO 220	84672200	16,400
0601B371F0	Bench Top Cut-off Saw	GCO 14-24	84672200	20,000
0601B372F0	Bench Top Cut-off Saw	GCO 14-24J (Soft-Start)	84672200	21,600
METALWORKING				
06012240F0	Straight Grinder	GGs 3000 L	84672900	10,300
06012241F0	Straight Grinder	GGs 5000 L	84672900	12,400
06012211F0	Straight Grinder	GGs 28 LCE	84672900	27,900
060127A3F0	Bench Grinder	GBG 35-15	84672900	13,000
060127A4F0	Bench Grinder	GBG 60-20	84672900	20,700
06014440F0	Impact Wrench	GDS 18 E	84672100	62,400
06014351F3	Impact Wrench	GDS 30	84672100	1,34,600

Part Number	Category	Model Number	HSN Code	MRP ₹
GRINDERS				
060137505F	Mini Grinder 4"	GWS 600	84672900	3,600
06013940F0	Mini Grinder 4"	GWS 750-100	84672900	4,900
06013960F0	Mini Grinder 4"	GWS 900-100	84672900	6,000
060137515A	Mini Grinder 5"	GWS 6-125	84672900	5,300
06013961F2	Mini Grinder 5"	GWS 900-125 S	84672900	7,800
06018242F1	Mini Grinder 5"	GWS 14-125 CI	84672900	11,300
06017A30F1	Mini Grinder 5"	GWS 18-125 L	84672900	17,570
06017C40F2	Mini Grinder with X-LOCK	GWX 17-125 S	84672900	20,100
06017760F0	Concrete Grinder	GBR 15 CAG	84672900	73,600
06018B70F0	Large Angle Grinder 7"	GWS 2000-180	84672900	11,000
06018C00F0	Large Angle Grinder 7"	GWS 2200-180	84672900	12,100
0 601 8C2 0F0	Large Angle Grinder 7"	New! GWS 24-180	84672900	15,155
0 601 8C2 3F0	Large Angle Grinder 7"	New! GWS 24-180 JZ	84672900	16,690
06018551F0	Large Angle Grinder 7"	GWS 26-180 H	84672900	26,500
06018C01F0	Large Angle Grinder 9"	GWS 2200-230	84672900	26,900
0601854455	Large Angle Grinder 9"	New! GWS 24-230 H	84672900	16,690
0 601 8C3 3F0	Large Angle Grinder 9"	New! GWS 24-230 JZ	84672900	17,845
06018561F0	Large Angle Grinder 9"	GWS 26-230 H	84672900	26,900
WOODWORKING				
06016B30F0	Circular Saw	GKS 140	84672200	10,500
06016230F1	Circular Saw	GKS 190	84672200	14,400
06015A20F0	Circular Saw	GKS 235 Turbo	84672200	18,700
06015A80F0	Jigsaw	GST 650	84672200	5,060
0 601 2A7 0F1	Jigsaw	GST 700	84672200	9,110
060158F0F0	Jigsaw	GST 90 BE	84672200	19,100
06015130F0	Jigsaw	GST 150 BCE	84672200	35,600
0601B450F0	Table Saw	New! GTS 254	84672200	35,600
0601B305F0	Table Saw	GTS 10 J	84672200	97,800
0601B290F0	Mitre Saw	GCM 10 MX	84672200	30,500
06015960F0	Planer	GHO 6500	84672900	10,500
06015940F1	Planer	GHO 10-82	84672900	11,600
06015A40F0	Planer	GHO 26-82 D	84672900	9,600
06013875F2	Random Orbit Sander	GEX 125-1 AE	84672900	9,600
06013728F0	Random Orbit Sander	GEX 34-150	84672900	20,200
06012A80F0	Orbital Sander	GSS 140	84672900	4,300
06012980F0	Orbital Sander	GSS 2300	84672900	8,100
06016A00F0	Router	GKF 550	84672900	7,700
06016B70F0	Router	GOF 130	84672900	13,900
06014A20F0	Screwdriver	GTB 650	84672900	11,600
STORAGE BOXES				
1600A001RV	Storage Boxes	i-BOXX 53	39231090	2,700
1600A001RW	Storage Boxes	i-BOXX 72	39231090	2,100
1600A012FZ	Storage Boxes	L-BOXX 102	39231090	3,700
1600A012G0	Storage Boxes	L-BOXX 136	39231090	3,800
1600A012G2	Storage Boxes	L-BOXX 238	39231090	5,200
1600A012G3	Storage Boxes	L-BOXX 374	39231090	6,900
1600A007SF	Storage Boxes	L-BOXX Mini	39231090	1,200
1600A001RU	Storage Boxes	L-BOXX 306	39231090	8,700
1600A00222	Storage Boxes	LT-BOXX 170	39231090	5,900
1600A00223	Storage Boxes	LT-BOXX 272	39231090	7,570
1600A003BJ	Tool Bag	TOOL BAG - 48 x 28 x 30	39231090	3,200
1600A003BK	Tool Bag	TOOL BAG - 55 x 35 x 35	39231090	3,700

WARRANTY TERMS AND CONDITIONS

Power Tools from Bosch are guaranteed against all material and manufacturing defects for a period of 6 months from the date of purchase* for Professional tools and 1 year from the date of purchase* for Professional Heavy Duty Tools.

In the event of failure of the tools due to material and manufacturing defects, we undertake to repair the tools free of charge, provided we are satisfied that:

- ▶ The power tool has not been tampered.
- ▶ Failure has occurred due to manufacturing / material defect.
- ▶ The power tool has been purchased from an accredited / authorized / recognized dealer.
- ▶ The claim has been referred to one of the Bosch Authorized Service Centres along with the Power Tool, guarantee card and original tool purchase receipt or invoice.

This warranty does not cover:

- ▶ All normal wear and tear parts like carbon brush, bearings, o-rings etc.
- ▶ Installation to wrong voltage, over load and wrong application.
- ▶ Use other than in accordance to handling instructions.
- ▶ Unauthorized repair carried out.
- ▶ Damage due to any unit caused by accident, misuse, wilful damage, and normal wear, claims arising from loss, fire or other calamities caused by nature or in any way being tampered with.

*Check with Local Bosch representative for Hot Air Gun Warranty.



BOSCH

Professional

6 months warranty from
the date of purchase*



BOSCH

Professional

**HEAVY
DUTY**

1 year warranty from
the date of purchase*







Bosch Limited, Power Tools Division

PA-AT Complex, Hosur Road, Adugodi,
Bangalore - 560030

 www.facebook.com/BoschPTIndia



Customer Contact Center

1800 425 8665

Email: bpt@in.bosch.com

www.bosch-pt.co.in

Edition: March 2022